





TADANO ATF70-G4 DRAAGLASTTABEL (met maximale ballastconfiguratie)

   11.9t + 3.1t Option = 15t DIN/ISO/EN											
 → m	11.0 m*	11.0 m	14.8 m	18.7 m	22.5 m	26.3 m	30.1 m	34.0 m	37.8 m	41.6 m	44.0 m
2.5	70.0**	58.0**									
3.0	59.6**	54.8**	50.0	49.3							
3.5	54.8**	49.7	47.0	45.1	42.3						
4.0	49.2	45.4	43.4	41.9	41.0	30.0					
4.5	43.5	41.6	40.3	38.9	38.0	30.0	24.5				
5.0	38.9	37.8	37.6	36.2	35.4	30.0	23.3	18.8			
6.0	31.9	31.8	32.0	31.5	31.2	28.8	21.1	18.8	14.2		
7.0	26.9	26.9	27.2	27.3	27.0	26.4	19.2	17.7	14.2	10.8	9.6
8.0	23.2	23.2	23.5	23.5	23.3	23.6	17.9	16.3	14.2	10.8	9.6
9.0			20.5	20.7	20.6	20.7	16.7	15.0	13.8	10.8	9.6
10.0			18.2	18.3	18.6	18.3	15.7	13.9	12.9	10.8	9.6
11.0			16.2	16.5	16.5	16.1	14.9	13.0	12.1	10.8	9.6
12.0			14.1	14.5	14.4	14.0	14.0	12.1	11.3	10.3	9.0
14.0				11.4	11.3	11.2	11.3	10.7	10.0	9.3	7.8
16.0				9.3	9.3	9.5	9.1	8.8	8.9	8.3	6.9
18.0					7.8	7.9	7.5	7.8	7.4	7.4	6.1
20.0					6.8	6.6	6.7	6.5	6.5	6.2	5.3
22.0						5.6	5.8	5.5	5.5	5.2	4.8
24.0							5.0	4.8	4.7	4.4	4.2
26.0							4.3	4.1	4.0	3.8	3.7
28.0								3.6	3.5	3.2	3.2
30.0								3.1	3.0	2.8	2.8
32.0									2.6	2.4	2.4
34.0									2.3	2.0	2.0
36.0										1.7	1.7
38.0										1.4	1.4
40.0											1.2

* Nach hinten / * Over rear / * A l'arrière / * Sobre la parte trasera

** Mit Zusatzhubausrüstung / ** With additional lifting equipment / ** Avec équipement supplémentaire / ** Con equipo adicional

TADANO ATF60-G4 DRAAGLASTTABEL + 9 meter JIP









11.9t + **3.1t** = **15t**
Option

DIN/ISO/EN

m	11.0 m + 9.0 m			30.1 m + 9.0 m			41.6 m + 9.0 m			44.0 m + 9.0 m		
	0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	40°
3.0	10.5*											
3.5	10.5*											
4.0	10.5*	10.5*										
4.5	10.5*	10.5*		10.5*								
5.0	10.5*	10.5*		10.5*								
6.0	10.5*	10.5*	8.9*	10.5*								
7.0	10.5*	9.9*	8.5	10.5*			6.0					
8.0	10.5*	9.4*	8.1	10.1*	8.1		6.0			5.4		
9.0	10.4*	8.9*	7.8	9.6*	7.7		6.0			5.4		
10.0	9.5*	8.5	7.5	9.0*	7.3	6.4	6.0			5.4		
11.0	8.7	8.2	7.2	8.5	7.0	6.1	6.0	5.4		5.4	5.1	
12.0	8.1	7.8	7.0	8.1	6.7	5.9	5.7	5.2		5.3	4.9	
14.0	7.1	7.2	6.7	7.3	6.2	5.5	5.2	4.9	4.4	4.9	4.6	4.3
16.0	6.3	6.8		6.7	5.8	5.2	4.8	4.5	4.2	4.5	4.3	4.0
18.0				6.0	5.4	4.9	4.4	4.3	3.9	4.2	4.0	3.8
20.0				5.4	5.1	4.7	4.1	4.0	3.7	3.8	3.8	3.6
22.0				4.8	4.8	4.5	3.8	3.7	3.5	3.6	3.5	3.4
24.0				4.3	4.4	4.3	3.6	3.5	3.4	3.3	3.3	3.2
26.0				3.6	3.8	4.0	3.2	3.3	3.2	2.9	3.0	3.0
28.0				3.1	3.2	3.4	2.9	3.0	3.0	2.6	2.7	2.7
30.0				2.6	2.8	2.8	2.6	2.7	2.8	2.3	2.4	2.4
32.0				2.2	2.3		2.3	2.4	2.5	2.0	2.2	2.2
34.0				1.9	1.9		2.0	2.1	2.2	1.8	1.9	2.0
36.0				1.6			1.6	1.8	1.9	1.6	1.7	1.8
38.0							1.4	1.5	1.6	1.3	1.5	1.5
40.0							1.1	1.2	1.3	1.1	1.2	1.3
42.0							0.9	1.0		0.9	1.0	1.0
44.0							0.7	0.8		0.7	0.8	
46.0							0.6	0.6		0.5	0.6	

* Mit Zusatzhubausrüstung / * With additional lifting equipment / * Avec équipement supplémentaire / * Con equipo adicional

TADANO ATF60-G4 DRAAGLASTTABEL + 16 meter JIP

 360° 11.9t + 3.1t = 15t DIN/ISO/EN													
	11.0 m + 16.0 m			30.1 m + 16.0 m			41.6 m + 16.0 m			44.0 m + 16.0 m			
	0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	40°	
3.0	7.9												
3.5	7.9												
4.0	7.9												
4.5	7.9												
5.0	7.9												
6.0	7.6			4.8									
7.0	7.2			4.8									
8.0	6.7	5.4		4.8			3.5						
9.0	6.3	5.1		4.8			3.5			3.3			
10.0	5.9	4.9		4.8			3.5			3.3			
11.0	5.6	4.7		4.8			3.5			3.3			
12.0	5.3	4.4	3.9	4.8	4.6		3.5			3.3			
14.0	4.7	4.1	3.7	4.8	4.4		3.5			3.3			
16.0	4.2	3.8	3.4	4.8	4.2	3.5	3.5	3.5		3.3			
18.0	3.7	3.5	3.3	4.8	4.0	3.4	3.5	3.3		3.3	3.1		
20.0	3.4	3.3	3.2	4.6	3.8	3.3	3.5	3.1		3.3	3.0	2.8	
22.0	3.1	3.2	3.1	4.3	3.6	3.2	3.2	2.9	2.7	3.0	2.8	2.6	
24.0	2.8	3.1		4.1	3.5	3.1	3.0	2.8	2.6	2.8	2.7	2.5	
26.0				3.7	3.3	3.0	2.8	2.7	2.5	2.6	2.5	2.4	
28.0				3.4	3.2	2.9	2.7	2.6	2.4	2.4	2.4	2.3	
30.0				2.9	3.0	2.8	2.5	2.4	2.3	2.1	2.2	2.2	
32.0				2.5	2.8	2.7	2.2	2.3	2.2	1.9	2.0	2.1	
34.0				2.1	2.4	2.6	2.0	2.2	2.1	1.7	1.8	1.9	
36.0				1.8	2.0	2.2	1.8	2.0	2.0	1.5	1.6	1.7	
38.0				1.6	1.7		1.5	1.8	1.9	1.4	1.5	1.5	
40.0				1.3	1.5		1.3	1.5	1.7	1.2	1.3	1.4	
42.0				1.1	1.2		1.1	1.3	1.4	1.0	1.2	1.3	
44.0				1.0			0.9	1.1	1.2	0.8	1.0	1.1	
46.0							0.7	0.8	0.9	0.6	0.8	0.9	
48.0							0.5	0.7		0.5	0.6	0.7	
50.0								0.5			0.5		